



High-Performance Integrated RFID Portal

General Features

- Specifically Designed for Monitoring Transition Zones and Passageways
- Ceiling or Wall Installation
- Compact and Easy to Install
- Aluminum Metal Enclosure with Electrostatic Coating

Compatible Readers (Not Included)

- Identix EZ500 and EZ700
- Impinj R700 and R720

Integrated Antenna Array

- Two Antenna Options
 - Antennas with Circular Polarization and 9 dBiC Gain
 - Antennas with Dual Linear Polarization (H+V) and 8.5 dBiC Gain

The Identix GateView OTP is a high-performance RAIN RFID portal featuring a compact, fully integrated design that combines the RFID reader and antennas into a single ready-to-use unit compatible with Identix and Impinj readers.

Designed for critical applications such as transition zones, large-area monitoring, and tag reading under challenging conditions, the GateView OTP provides high transmission power, advanced sensitivity, and leverages the high gain and efficiency of Identix antennas, ensuring maximum performance even in complex scenarios.


When used with tags equipped with the Impinj M800 chip, the GateView OTP supports the GEN2X protocol, enabling a significant performance improvement with up to a 90% reduction in inventory time for Tags of Interest (TOI).

Featuring a discreet finish, compact dimensions, and flexible installation options — including mounting on ceilings, walls, or custom structures — the GateView OTP is ideal for a broad range of applications across retail, logistics, industry, and other sectors.



Technical Specifications

- Integrated RAIN RFID portal with reader (not included) and antennas
- Compatible readers:
 - Identix EZ500 and EZ700
 - Impinj R700 and R720
- Two Antenna Options
 - Circular polarization with 9 dBiC gain
 - Dual linear polarization (H+V) with 8.5 dBiL gain
- Allows installation of a second GateView or two additional antennas when used with circular polarization antennas
- Full reading zone coverage
 - With Identix reader 80° x 90° (A+B = 80°)
 - With Identix reader 70° x 90° (A+B = 70°)
- Wall or ceiling mounting
- Ceiling mounting bracket included
- Environmental protection rating: IP54
- Operating temperature: -20°C to +50°C and humidity between 5% and 95%
- Dimensions: 455 x 450 x 50 mm
- Approximate weight: 4 kg



For more information, visit
identix.com.br